



# HD Series Industrial Steel Units

## Meets New York City Requirements

### Description

6 and 12 volt emergency lighting units in capacities up to 340 watts featuring traditional style, maintenance-free batteries and rugged steel construction.

### Features

- 6 and 12 volt models
- 85 to 340 watt capacities
- Heavy gauge steel cabinet in neutral cream finish
- Fully adjustable thermoplastic lighting heads with locking swivel assemblies
- Maintenance-free lead calcium battery standard
- 90 Minutes of emergency illumination
- Universal 120/277VAC input
- Fully automatic, temperature compensating, variable rate float charger standard
- Automatic low voltage battery disconnect protects battery from deep discharge
- Automatic brownout protection
- AC lockout feature reduces installation time
- Optional self-diagnostic circuit available
- Momentary test switch, AC ready and high charge indicators
- Meets NFPA Life Safety Code 101, NEC, OSHA, Local and State Codes
- UL924 listed



### Ordering Guide

Model No.	Volts	Watts For 1 1/2 Hrs.	Watts For 2 Hrs.	Watts For 3 Hrs.	Watts For 4 Hrs.	Standard Lamp	Weight (Lbs.)
HD-2	6	85	67	47	37	7.2W (-03)	35
HD-4	6	100	79	56	44	7.2W (-03)	40
HD-6	6	152	120	85	66	7.2W (-03)	60
HD-8	6	210	165	117	92	7.2W (-03)	75
12HD-13	12	170	134	95	74	9W (-51)	45
12HD-15	12	210	165	117	92	9W (-51)	65
12HD-17	12	340	268	190	149	9W (-51)	75

#### Options <sup>(1)(2)</sup>

Add Suffix	Description
-V	Voltmeter
-A	Ammeter
-LC1	3-Conductor Line Cord (120V)
-TD1	15-Minute Re-transfer Time Delay (120V)
-TD2	15-Minute Re-transfer Time Delay (277V)
-220	220V, 50Hz Input
-SX	Self-Diagnostic Circuit
-MH	Metal Lighting Heads
-B	Black Finish - Housing and Lighting Heads
-SP	Special Paint Finish - Specify Color

#### Accessories

Order Model	Description
B-1	Mounting Bracket (HD-2, 4, 6 and 12HD-13 models)
S-4	Mounting Shelf (HD-2, 4, 6 and 12HD-13 models)
S-5	Mounting Shelf (HD-8, 12HD-15 and -17 models)
PG-2	Wire Guard (all models)
900-W-03	Matching Remote Head-Single (6 Volt models) (6V, 7.2W)
900-W-51	Matching Remote Head-Single (12 Volt models) (12V, 9W)
901-W-03	Matching Remote Head-Double (6 Volt models) (6V, 7.2W)
901-W-51	Matching Remote Head-Double (12 Volt models) (12V, 9W)

NOTE: All product specifications shown are subject to change without notice.

(1) Other options available. Consult factory.

(2) Some options may impact product UL listing. Consult factory.

### Specifier Reference

